# LJUSi/FOKUS

### **LED Ceiling Light**





#### 1. Product Parameter

| Model       | Color Temperature | Lumen  | Working Voltage | Power | Size       | IP Class |
|-------------|-------------------|--------|-----------------|-------|------------|----------|
| WDM-CL-0301 | 2700-6500K        | 1100lm | AC220-240V      | 15W   | Ф325*100mm | 65       |
| WDM-CL-0302 | 2700-6500K        | 1300lm | AC220-240V      | 18W   | Ф325*100mm | 65       |

#### 2. Features

- 1). Long life time to 40,000hr.
- 2). With internal Constant Current Power Supply.
- 3). 120° beam angle makes the lighting effect better.
- 4). High quality PC material is of anti-UV radiation, durable, not prone to yellow.
- 5). Use the most mature international well-known LED SMD2835 as the light source, which can ensure the led ceiling light brightness and long lifetime, also can reduce the light decay.
- 6). No mercury, lead or other hazardous materials; no radiation, no electromagnetic radiation, no frequency flash, instant startup, no hurting eyes.





## 3. Application

Bathroom; Living Room; Bedroom; Kitchen;

Restaurant; Hotel; Bank; Hospital; Etc.









### 4. Installation


(need to be installed by professional people)




Step1 Strip down the housing and the PCB panel



Step2 Drill the screw hole and link power




Step3 Install the setscrew and fix the bass plate on the ceiling



Step4 Recover the PCB panel and the housing

#### 5. Product Details



Diameter: 325mm

Thickness: 100mm







**Stress Test** 





# 6. Packaging













| Model         | Single Box | PCS/CTN | N.W./CTN(kg) | G.W./CTN(kg) | Meas(cm)   |
|---------------|------------|---------|--------------|--------------|------------|
| Ceiling Light | 1          | 12      | 11           | 12           | 65.5*34*67 |